

PRECISION BALANCE JT



Moorrange
Precision Your Weighing

Moorrange
Precision Your Weighing

Features

- > Professional design
- > JT103 with HBM* load cells
- > FSTN LCD display
- > Clock set
- > Zero/Tare
- > Stainless steel pan
- > RS232 interface
- > Multi-units: g/ct/lb/oz/GN/dwt...
- > Piece counting
- > Checkweigh function
- > Animal weighing
- > Accumulation
- > OTH gsm/gdm/ozt weighing
- > Percentage weighing
- > Big capacity till 2100g
- > Below weighing optional
- > Windshield optional (0.01g|0.001g)
- > Bluetooth optional


Accessories

- > Remote display - JTRD
- > Statistics printer - XT110
- > Label printer - T40
- > Balance Table I - 900 x 600mm
- > Balance Table II - 1200 x 600mm

*HBM logo and all copyrights belong to
Hottinger Baldwin Messtechnik GmbH


TechnicalData

Power 100-240VAC 50/60Hz - DC9V/500mA Or 9V battery	Repeatability ±0.5g (≤500g) ±1.0g (≤2000g) ±1.5g (>2000g)
Capacity 100g-2100g	S.S Pan (Dia) 110mm (0.01g 0.001g) 160mm (0.1g)
Division 0.1g/0.01g/0.001g	Overall Dimensions 225*175*75mm
Display LCD	Windshield (optional) dia 140mm
Interface: RS232	Weight 1.6kg
Units g/ct/lb/oz/GN/dwt...	



Models

Part No.	101130	101131	101132	101133	101134	101135	101136	101137
Models	JT103	JT202	JT302	JT502	JT601	JT1201	JT2101	JT3101
Capacity	100g	200g	300g	500g	600g	1200g	2100g	3100g
Division	0.001g		0.01g				0.1g	
S.S Pan		Dia 110mm				Dia 160mm		
Weight					1.6kg			



CF S.S CRANE SCALE

SUS304 S.S Housing

Easy for operation, suitable for food industry, farms, warehouse, dock, factory, etc.

- SUS304 stainless steel housing
- SUS304 stainless steel hook
- Rechargeable 6V1.2Ah battery
- optional 7.4V6.8Ah Ni-MH battery
- 1" Bright LED display
- Big capacity till 600Kg
- OIML R76 Class III accuracy
- Kg/lb units exchange
- Remote control ≤15m
- Tare range: 10%-100%F.S.
- Power saving mode
- Remote control with 4 keys:
- Function/Tare/Accumulate/Hold**
- Three direct keys:
- Tare/Hold/On/Off**
- Gravity adjusting

Accessories

- Optional Bluetooth output
- Optional Bluetooth printer
- Optional wireless remote display
- Optional s.s hanging pan (for CF30)
- Optional aluminum suitcase
- Optional stainless steel swivel hook



No.4	
Gross:	47kg
Tare:	4kg
Net:	43kg

Power

100-240V - 12V adaptor

Battery

Battery: 6V1.2Ah
- optional 7.4V6.8Ah Li-ion

Capacity

30 - 600kg

Accuracy

Class III

Housing

SUS304

Protection

IP54

Safety Load

120% F.S.

Display

1" LED (25mm)

Stable Time

≤8s

Unit

kg | lb

Tare Range

100% F.S.

Output

Bluetooth (optional)

Operating Temperature

-10°C - 40°C

Weight

2.6kg

Models

Part No.	100601	100602	100603	100604	100605
Models	CF30	CF60	CF150	CF300	CF600
Capacity	30kg	60kg	150kg	300kg	600kg
Division	10g	20g	50g	100g	200g
Weight	2.5kg	2.5kg	2.5kg	2.6kg	2.6kg