

RETAIL SCALE PC6S



Moorange
Precision Your Weighing



TechnicalData

Power 100-240V - 12V1A adaptor Rechargeable Battery: 6V4Ah Estimated working time: 130hrs - no backlit 60hrs - with backlit	Display LCD with backlit	PLU 40 (20 direct)
Pan Dimensions 315 x 250mm	Units Kg lb g oz, etc.	Operating Temperature -10°C - 40°C ≤80% non-condensing
Capacity 3 6 15 30Kg	Sampling Speed 20 times/second	Storage Temperature -25°C - 55°C ≤80% non-condensing
Display Resolution 1/3,000	Non-linearity ≤0.01%F.S.	Approval CE EC Type (pending)
Net Weight 6kg	Power Consumption 30mA - no backlit 65mA - with backlit 77mA - with backlit RS232	RS232 Optional

Features

Stainless steel housing <
Big s.s pan 315 x 250mm <
Aluminum load cell supporter <
Big LCD display with backlit <
Rechargeable 6V battery <
- 130hrs operating time (no backlit)
Dual range capacity <
3-window rear display <
40 PLU (20 direct) keys <
Multi-units for selection <
Money-change function <
Fixed value function <
Price calculating per qty <
Zero and full capacity tare <
Accumulating function <
Memory recall and clean <
Gravity value setup <
Auto power off <
RS232 optional <
WiFi optional <
Bluetooth optional <
Customized protocol optional <

Models

Part No.	100878	100879	100880	100881
Models	PC6S15	PC6S30	PC6S15M	PC6S30M
Capacity	6/15kg	15/30kg	6/15kg	15/30kg
Division	2/5g	5/10g	2/5g	5/10g
Pack Size	78 x 45 x 35cm (4pcs)			
Weight	26kg (4pcs)			

Moorange
Precision Your Weighing



CSS COUNTING SCALE



TechnicalData

Power 100-240V - 12V1A adaptor Rechargeable Battery: 6V4Ah Estimated working time: 320hrs	Display LCD with backlight	Power Consumption 12mA - no backlit 36mA - with backlit
Pan Dimensions 315 x 250mm	Units Kg lb	Operating Temperature 0°C - 40°C
Capacity 3 6 15 30Kg	Shortcut U.W. 40 Memories	Approval CE
Division 0.1 0.2 0.5 1.0g	Sampling Speed 20times/second	RS232 Optional
Net Weight 6Kg	Non-linearity ≤0.01%F.S.	

Features

Stainless steel housing <
Big s.s pan 315 x 250mm <
Big LCD display with backlit <
Rechargeable 6V battery <
4 height adjusting feet <
High accuracy of 1/30,000 <
Multi-units exchange <
40 PLU of unit weight <
Weight accumulation <
Unit weight recalculate <
Recall of memory weight <
Auto power off setup <
Optional RS232 interface <
Optional Bluetooth output <

Models

Part No.	100820	100821	100822	100823
Models	CSS3	CSS6	CSS15	CSS30
Capacity	3kg	6kg	15kg	30kg
Division	0.1g	0.2g	0.5g	1g
Pack Size	78 x 45 x 35cm (4pcs)			
Weight	26kg (4pcs)			